



生产注意事项

TYPE C3.1 公头焊接面

技术要求	
线材规格	
接触数量	16
温度范围	-25°C~+80°C
耐电压	≥DC300V
绝缘电阻	≥10 MΩ DC300V

Pin Assignment 接线定义		
P1		P2
A4		A4
A9		A9
B4		B4
B9		B9
A1		A1
A12		A12
B1		B1
B12		B12
外壳		外壳
B5		B5
A5		A5
A6		A6
A7		A7
A8		A8
B8		B8
A2		A2
A3		A3
B10		B10
B11		B11
B2		B2
B3		B3
A10		A10
A11		A11

TYPE C3.1 母头焊接面

No.	Specification	Unit	Q'ty
4	E13 塑胶六角螺母13/16-28UNS (28.6-25.4-4单边倒角) (A140300-0021)	pc	1
3	E13 塑胶端子防水垫片φ24.8×φ20.6×1.5 (A140100-0105)	pc	1
2	Type C 面板型板前安装母座塑料外壳 (正成logo) (A130202-0830)	pc	1
1	定制TYPE C 3.1公头转TYPE C 3.1母头, 通过FPC软板连接, 全长L= x M, TYPE C 公头使TYPE-C -CM 黑色胶芯 拉伸式铁壳 镀镍, TYPE C母头: TYPE-C -CF 黑色胶芯 铆合铁壳 镀镍, FPC软板: 黄色软性线路板 叠构: 4层线路, 接线定义: A4/A9/B4/B9-A4/A9/B4/B9, 外壳/A1/A12/B1/B12-A1/A12/B1/B12/外壳, B5-B5, A5-A5, A6-A6, A7-A7, A8-A8, B8-B8, A2-A2, A3-A3, B10-B10, B11-B11, B2-B2, B3-B3, A10-A10, A11-A11 (A180100-0115)	pc	1

GENERAL TOLERANCE (UNLESS SPECIFIED)		Specification		
≤10 ±0.1	DWN			
<10~≤20 ±0.2	CHK			
<20~≤50 ±0.5	APVD			
Angle ±1°		UNIT	REV	
		MM	A	
		SIZE	SHEET	
		A4	1 OF 1	
				TITLE
				EP-FT3.1-PWF/MT3.1-NWA-xFPC
				PART NO
				DRAWING NO

声明: 请贵司在2个工作日内确认并回传图纸, 过期未回传的, 默认为贵司已确认合格

业务确认

客户	图号	日期	制图	审核
		2024-07-09	胡俊明	
料号		单位: mm	Size:A4	
品名				

RoHS