


A	技术 参 数	芯数	2	3	4	5	5A	6	7	7A	8	12	14	14A	19	24
		额定电流/电压	7A/250V	7A/250V	6A/250V	6A/250V	6A/250V	5A/250V	5A/125V	5A/125V	5A/60V	3A/60V	3A/60V	3A/60V	3A/60V	1A/60V
		额定脉冲电压	1500V	1500V	1500V	1500V	1500V	1500V	800V	800V	800V	500V	500V	500V	500V	500V
		绝缘电阻(MΩ)	≥100	≥100	≥100	≥100	≥100	≥100	≥100	≥100	≥100	≥100	≥100	≥100	≥100	≥100
		接触电阻(mΩ)	≤5	≤5	≤5	≤5	≤5	≤5	≤5	≤5	≤5	≤5	≤3	≤3	≤3	≤3
B	芯位排布															
D	6	M16 焊线式母针	磷铜	镀金	pc	2~24	GENERAL TOLERANCE (UNLESS SPECIFIED) ≤10 ±0.1 <10~≤20 ±0.2 <20~≤50 ±0.5 Angle ±1°  THIRD ANGLE	DWN W.M	DATE 2022.10.8							
	5	M16 板前安装插座母头外壳	黄铜	镀镍	pc	1		CHK	DATE							
	4	M16 圆形螺母 M18×0.75	黄铜	镀镍	pc	1		APVD	DATE	TITLE M16 板前安装孔型插座						
	3	M16 法兰座外壳专用O型圈 Φ17×Φ14×1.5	橡胶	/	pc	1		UNIT MM	REV A	PART NO						
	2	M16 母头胶芯防水垫片 Φ14.7×Φ11×1.5	硅胶	/	pc	1		SIZE A4	SHEET 1 OF 1	DRAWING NO M16-B-Sx						
1	M16 常规母胶芯	尼龙	/	pc	1											
No.	Specification	Material	Treat	Unit	Q'ty											