





1) Product main performance/产品主要性能指标

Endurance (Shell)/壳体拔插次数: 5000  
 Operating Temperature/工作温度: -55° C~+200° C  
 Humidity(max)/最大潮湿:<=95% [at 60 deg C / 140 F]  
 Vibration/振动:15 g [10 Hz - 2000 Hz]  
 Shock Resistance/冲击:100 g [ 6 ms]  
 Salt Spray Corrosion/盐雾:>144 hr  
 Shielding (min)/屏蔽性能:75 dB (10 MHz)  
 Shielding(min)/屏蔽性能:40 dB (1 GHz)  
 P op(max)/最大环境压力:60 bar (870 psi)


OTHER CHARACTERISTICS /其他性能

Housing Material/壳体材料: 外壳体为铜合金, 表面镀铬镍  
 Insulator/绝缘体材料:PPS  
 Contact PIN/接触针芯: Gold plated Tin bronze/锡青铜镀金  
 IP rating(when mated)/防水等级(插合时): IP50





Alignment key  
定位销 (键位)  
插座前视图

键位	键位数量	角度
G	1	0°
A	2	α
B	2	
C	2	60°
D	2	β
E	2	
F	2	135°
J	2	145°
K	2	γ
		45°
		70°




建议开孔尺寸


2) Part Numbering System/产品编号原则




302 PCB




303 PCB




304 PCB




305 PCB




306 PCB



307 PCB



308 PCB



310 PCB

Insert Configuration 针芯配置	302	303	304	305	306	307	308	310
Pin Number (View N) 针芯排列N向								
Pin Size 接触体直径 (mm)	1.3	1.3	0.9	0.9	0.7	0.7	0.7	0.5
Withstand voltage 耐电压 (KV) (AC)	1500	1300	1300	1250	1050	950	950	900
Rated Current 额定电流 (A)	15	12	10	9	7	7	5	2.5
Insulation resistance 绝缘电阻 (MΩ)	≥5000MΩ							
R (max) 接触电阻 (mΩ)	5	5	6	6	7.5	7.5	7.5	10

TOLERANCES UNLESS OTHERWISE SPECIFIED:  
 Unmarked dimensional tolerances: ± 0.1  
 unmarked angular tolerances: ± 0.2°  
 除非特别说明:  
 未标注尺寸公差: ± 0.1  
 未标注角度公差: ± 0.2°

名称 PART NAME	1B-ZP Socket (2~8)		重量 QUALITY	单位 UNIT	比例 SCALE	标记 MARKING	
	图号 DRAWING NO.						
	设计 DESIGNED	校对 CHECKED					审核 APPROVED
	LTB	PWZ					YJ

重量 单位 比例 标记  
 QUALITY UNIT SCALE MARKING  
 mm 1: 1  
**CAZN 正成**



A4